

## SCHWEGO<sup>®</sup> foam 6305

### Defoamer and deaerator for water-based coating systems

**Chemical base:** Emulsion of a polymer, containing silicone oil

**Properties:** **SCHWEGO<sup>®</sup> foam 6305** is highly effective for prevention, control and elimination of foam and pinholes in aqueous media.

**Applications:** **SCHWEGO<sup>®</sup> foam 6305** is suitable in most water-based systems. Main application field of **SCHWEGO<sup>®</sup> foam 6305** are coating systems with low pigment content and clear coats. Using area are wood coatings, high gloss paints, parquet floorings, industrial coatings and adhesives.

**Technical data:**  
(Guide values)

Appearance	:	white, milky liquid
Density (ISO 2811-1)	:	1.00 g/cm <sup>3</sup>
Active matter	:	75 %

**Processing:** **SCHWEGO<sup>®</sup> foam 6305** can be used as supplied or prediluted. In case of predilution the water must be added slowly at low mixing. The optimum dosage of **SCHWEGO<sup>®</sup> foam 6305** is 0.01 - 0.5 %, calculated on total system. **SCHWEGO<sup>®</sup> foam 6305** is easily incorporated and chemically inert.

**Storage:** Do not store **SCHWEGO<sup>®</sup> foam 6305** at temperatures below 0 °C. Stir it up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **SCHWEGO<sup>®</sup> foam 6305** remain stable for at least 12 months, provided the original container is closed after use.

**Packaging:** 25 kg / 50 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.  
Further safety instructions please learn from our material safety data sheet. 03/2019