

## SCHWEGO<sup>®</sup> foam 6351

Deaerating additive for solvent borne, water-based and solvent free coating systems, silicone-free

**Chemical base:** Polymer in solvent mixture

**Properties:** **SCHWEGO<sup>®</sup> foam 6351** influences the surface tension in solvent based and solvent free systems and thus improves levelling, prevents cratering, punctures towards the substrate and blistering.

**Applications:** **SCHWEGO<sup>®</sup> foam 6351** is suitable for almost all solvent based and solvent free coating systems. It is particularly effective in hammer tone finishes and structural coatings, reactive thick film systems, heavily pigmented coating systems and formulations, suitable for airless spraying. **SCHWEGO<sup>®</sup> foam 6351** is also effective in aqueous industrial finishes (alkyd/melamine systems).

<b>Technical data:</b> (Guide values)	Appearance	: colourless opal liquid
	Density (ISO 2811-1)	: 0.86 g/cm <sup>3</sup>
	Flash point (ISO 1523)	: 27 °C
	Active matter	: 100 %

**Processing:** The dosage of **SCHWEGO<sup>®</sup> foam 6351** is 0.5 – 2.0 % calculated on total system. **SCHWEGO<sup>®</sup> foam 6351** can be incorporated at any stage of the production or subsequently. Application range and dosage should be investigated by laboratory tests.

**Storage:** Stir **SCHWEGO<sup>®</sup> foam 6351** up before use. Keep it in a cool, well-ventilated place. Subject to appropriate storage, the described properties of **SCHWEGO<sup>®</sup> foam 6351** remain stable for at least 18 months, provided the original container is closed after use.

**Packaging:** 50 kg / 175 kg drum

The above information is based on our current knowledge and experience. No binding assurance in respect of certain properties or suitability for certain applications must be read into our information. Patent rights and other proprietary rights must be observed if necessary.  
Further safety instructions please learn from our material safety data sheet. 03/2019