## schwegmann 🕻

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) : Supersedes date :

4.0.0 (3.1.0) 25.07.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1 Product identifier SCHWEGO<sup>®</sup> mar 8300 (8300) 1.2 Relevant identified uses of the substance or mixture and uses advised against **Relevant identified uses** Slip additive 1.3 Details of the supplier of the safety data sheet Supplier (manufacturer/importer/only representative/downstream user/distributor) Bernd Schwegmann GmbH & Co. KG Street : Wernher-von-Braun-Str. 14 Postal code/city: DE-53501 Grafschaft-Gelsdorf Telephone: +49 22 25 / 92 26-0 Telefax: +49 22 25 / 92 26-48 e-mail address of competent person for MSDS: MSDS@SchwegmannNet.de 1.4 Emergency telephone number +49 (0) 61 31 / 19 24 0 (POISON CENTER, 24 h in English and German) **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Category 2 ; Toxic to aquatic life with long lasting effects.

Asp. Tox. 1 ; H304 - Aspiration hazard : Category 1 ; May be fatal if swallowed and enters airways.

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Irrit. 2 ; H315 - Skin corrosion/irritation : Category 2 ; Causes skin irritation.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H335 - STOT-single exposure : Category 3 ; May cause respiratory irritation.

STOT SE 3 ; H336 - STOT-single exposure : Category 3 ; May cause drowsiness or dizziness.

## 2.2 Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



Flame (GHS02) · Health hazard (GHS08) · Corrosion (GHS05) · Environment (GHS09) · Exclamation mark (GHS07) **Signal word** 

Danger

## Hazard components for labelling

Hydrocarbons, C9, aromatics / Solvent naphtha

2-Methylpropan-1-ol

## Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.

## SCHWEGmann 🕻

Trade name :	SCHWEGO <sup>®</sup> mar 8300		
Revision date :	25.07.2018	Version (Revision) :	4.0.0 (3.1.0)
Print date :	25.07.2018	Supersedes date :	25.07.2018

H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
Precautionary state	ements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

## 2.3 Other hazards

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

## **SECTION 3: Composition / information on ingredients**

#### 3.2 Mixtures

#### Hazardous ingredients

2-Methylpropan-1-ol ; REACH registration No. : 01-2119484609-23 ; EC/List No. : 201-148-0; CAS No. : 78-83-1

2-hethypiopar-1-0, REACT registration No 01-2119-0-009-25, EC/List No 201-140-0, CAS No 70-03-1				
Weight fraction :	≥ 25 - < 35 %			
Classification 1272/2008 [CLP] :	Flam. Liq. 3 ; H226 Eye Dam. 1 ; H318 Skin Irrit. 2 ; H315 STOT SE 3 ; H335 STOT SE 3 ; H336			
Hydrocarbons, C9, aromatics / Solvent naphtha (petroleum), light arom. (Benzene < 0,1 %) ; REACH registration No. : 01- 2119455851-35 ; EC/List No. : 918-668-5; CAS No. : 64742-95-6				
Weight fraction :	≥ 25 - < 35 %			
Classification 1272/2008 [CLP] :	Flam. Liq. 3; H226 Asp. Tox. 1; H304 STOT SE 3; H335 STOT SE 3; H336 Aquatic Chronic 2; H411			
Additional information				

Full text of H- and EUH-phrases: see section 16.

#### 3.3 Additional information

Materials that are listed in the so-called "Candidate List of Substances of Very High Concern (SVHC) for authorisation<sup>3</sup> ", issued by the ECHA, are not intentionally any part of this product. It is therefore not to be expected that such materials are present in quantities  $\geq 0,1$  % in the product.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

#### **General information**

Remove contaminated, saturated clothing immediately. When in doubt or if symptoms are observed, get medical advice.

### **Following inhalation**

Provide fresh air.

In case of respiratory tract irritation, consult a physician.

## In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin reactions, consult a physician.

#### After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. Protect uninjured eye.

### After ingestion

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) : Supersedes date :

SCHWEGMann 🗲

4.0.0 (3.1.0) 25.07.2018

Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person or a person with cramps. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

- **4.2 Most important symptoms and effects, both acute and delayed** See section 2.
- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

## **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

### Suitable extinguishing media

alcohol resistant foam. Carbon dioxide (CO2). Extinguishing powder. Water mist

Unsuitable extinguishing media Full water jet

## 5.2 Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide. Carbon dioxide  $(CO_2)$ . Possible in traces: Formaldehyde

The formation of combustible vapours is possible at temperatures above: 15 °C

## 5.3 Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

## 5.4 Additional information

Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

## For non-emergency personnel

Remove persons to safety. Provide adequate ventilation. See protective measures under chapter 7 and 8.

### For emergency responders

Prevent spread over a wide area (e.g. by containment or oil barriers). Personal protection equipment: see section 8

## 6.2 Environmental precautions

Clear spills immediately. Do not allow to enter into soil/subsoil. Cover drains. Do not allow to enter into surface water or drains.

## 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Take up mechanically, placing in appropriate containers for disposal.

### **Other information**

Special danger of slipping by leaking/spilling product.

## 6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13

## schwegmann 🕻

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) : Supersedes date : 4.0.0 (3.1.0) 25.07.2018

## **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

### Protective measures

When using do not eat, drink, smoke, sniff.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500<sup>1</sup>. **Measures to prevent fire** 

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Remove all sources of ignition. Take precautionary measures against static discharges. Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.

Ignition	group :	
Fire class	5:	

## Fire class : B 7.2 Conditions for safe storage, including any incompatibilities Technical measures and storage conditions

T2

#### rechnical measures and storage conditions

Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Floors should be impervious, resistant to liquids and easy to clean. No ground outlets on containers.

## **Packaging materials**

Keep/Store only in original container.

### Requirements for storage rooms and vessels

Protect containers against damage.

## Keep in a cool, well-ventilated place.

## Hints on joint storage

Keep away from: Oxidising agent

Storage class (LGK): 3

### Further information on storage conditions

Observe technical data sheet.

## 7.3 Specific end use(s)

Further information: see technical data sheet.

## SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

## **Occupational exposure limit values**

2-Methylpropan-1-ol ; CAS No. : 78-83-1 Limit value type (country of origin) : TRGS 900 ( D ) Limit value : 100 ppm / 310 mg/m<sup>3</sup> Peak limitation : 1(I) Remark : DFG, Y Version : 01.01.2006 Hydrocarbons, C9, aromatics / Solvent naphtha (petroleum), light arom. (Benzene < 0,1 %); CAS No. : 64742-95-6 Limit value type (country of origin) : TRGS 900 ( D ) (RCP-Method) Parameter : Limit value : 50 mg/m<sup>3</sup> Peak limitation : 2(II) Remark : AGS 01.09.2017 Version: Remark Y: A risk of reproductive effects needs not to be feared if the occupational exposure limit value (AGW) and the

## biological limit value (BGW) is kept Recommended monitoring procedures

See the series of publications by the German Federal Institute for Occupational Safety and Medicine (Bundesanstalt für

Page : 4 / 10

## SCHWEGmann 🕻

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) : Supersedes date :

4.0.0 (3.1.0) 25.07.2018

Arbeitsschutz und Arbeitsmedizin - BAuA)<sup>1</sup> and BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents."

## 8.2 Exposure controls

## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

## Personal protection equipment

## Eye/face protection

Eye glasses with side protection

### Skin protection

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

### Hand protection

Suitable material : FKM (fluoro rubber)

Breakthrough time (maximum wearing time) : > 7200 s (LEVEL 4)

## Thickness of the glove material (mm) : 0,7

Additional hand protection measures : Wear cotton undermitten if possible.

**Remark** : For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

## **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Combination filtering device (EN 14387) A - P 2

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

### Appearance

Physical state : liquid

Colour : clear , colourless

### Odour

characteristic

## Safety relevant basis data

-					
Flow time :	(23 °C)	>	35	S	ISO 2431 (Flow cup 3 mm)
Melting point/melting range :	(1013 hPa)	<	-5	°C	
Initial boiling point and boiling range :	(1013 hPa)	>	100	°C	Literature value
Decomposition temperature :			No data available		
Flash point :			30	°C	ISO 1523
Ignition temperature :		>	350	°C	DIN 51794
Lower explosion limit :			0,7	Vol-%	Literature value
Upper explosion limit :			10,6	Vol-%	Literature value
Vapour pressure :	( 50 °C )	<	0,1	bar	(calculated)
Density :	( 20 °C )		0,89 - 0,91	g/cm <sup>3</sup>	ISO 2811-1
Vapour density :	( 20 °C )		No data available		
Relative density (aqua = 1) :	( 20 °C )		0,89 - 0,91		
Water solubility :	( 20 °C )	<	300	g/l	(calculated)
log P <sub>o/w</sub> :			No data available		Literature value, solvent
Kinematic viscosity :	(40 °C)	<	15	mm²/s	ISO 3105
Odour threshold :	. ,		No data available		
Vapourisation rate :			No data available		Literature value,

## schwegmann 🕻

Trade name :	SCHWEGO <sup>®</sup> mar 8300		
Revision date :	25.07.2018	Version (Revision) :	4.0.0 (3.1.0)
Print date :	25.07.2018	Supersedes date :	25.07.2018

Maximum VOC content (EC) : Maximum VOC content (Switzerland) :		50 50	Wt % Wt %	solvent Directive 2010/75/EU (calculated)
Flammable solids :	No data available.			
Oxidising liquids :	Not oxidising.			
Explosive properties :	Not explosive according to EU A.14.			

## 9.2 Other information

The VOC concentration was calculated by a method analogical to standard ISO11890-1. The designation of explosive limits refers to the flammable mixture constituents and not to the overall product. Additional physical-chemical data are not available / have not been determined.

## **SECTION 10: Stability and reactivity**

## 10.1 Reactivity

There are no data available on the mixture itself.

### 10.2 Chemical stability

The product is chemically stable under normal ambient conditions (+20° C room temperature).

## **10.3 Possibility of hazardous reactions**

No known hazardous reactions.

## **10.4 Conditions to avoid**

Only use the material in places where open light, fire and other flammable sources can be kept away.

## **10.5 Incompatible materials**

Oxidising agent

## **10.6 Hazardous decomposition products**

In case of warming: Vapours can form explosive mixtures with air. >  $150^{\circ}$  C Formation of: Formaldehyde

## **SECTION 11: Toxicological information**

## 11.1 Information on toxicological effects

### Acute effects

Acute oral toxicity Mixture not tested. Acute dermal toxicity Mixture not tested. Acute inhalation toxicity Mixture not tested.

### Irritant and corrosive effects

Skin corrosion/irritation : Mixture not tested. Serious eye damage/eye irritation : Mixture not tested.

## Sensitisation

Specific effects: Mixture not tested.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP. **Germ cell mutagenicity** 

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP. **Reproductive toxicity** 

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP. **STOT-single exposure** 

## Page : 6 / 10

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) : Supersedes date :

SCHWEGMann 🗲

4.0.0 (3.1.0) 25.07.2018

## Mixture not tested.

STOT-repeated exposure

## Mixture not tested. Aspiration hazard

Hydrocarbon content (%): > 10 % Cinematic viscosity (40°C): < 20,5 mm<sup>2</sup>/s

## **SECTION 12: Ecological information**

## 12.1 Toxicity

There are no data available on the mixture itself.

## Effects in sewage plants

The polymer component: The product can be eliminated from water by abiotic processes, e.g. adsorption on activated sludge.

## 12.2 Persistence and degradability

Solvent : Readily biodegradable (according to OECD criteria).

## 12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

## 12.4 Mobility in soil

If product enters soil, it will be mobile and may contaminate groundwater.

## 12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

## 12.6 Other adverse effects

Ozone depletion potential (ODP): This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].

## Additional ecotoxicological information

None

## **SECTION 13: Disposal considerations**

## 13.1 Waste treatment methods

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains.

## Product/Packaging disposal

Consult the appropriate local waste disposal expert about waste disposal.

Waste codes/waste designations according to EWC/AVV

16 03 05

## Waste code packaging

15 01 10

#### Waste treatment options Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning.

## **SECTION 14: Transport information**

## 14.1 UN number

UN 1263

## 14.2 UN proper shipping name

Land transport (ADR/RID) PAINT RELATED MATERIAL

Sea transport (IMDG)

## schwegmann 🕻

Trade name :	SCHWEGO <sup>®</sup> mar 8300		
Revision date :	25.07.2018	Version (Revision) :	4.0.0 (3.1.0)
Print date :	25.07.2018	Supersedes date :	25.07.2018

	PAINT RELATED MATERIAL (SOLVENT NA Air transport (ICAO-TI / IATA-DGR)	APHTHA, LIGHT )		
	PAINT RELATED MATERIAL			
14.3	Transport hazard class(es)			
	Land transport (ADR/RID)			
	Class(es) :	3		
	Classification code :	F1		
	Hazard identification number (Kemler			
	No.):	30		
	Tunnel restriction code :	D/E		
	Hazard label(s) :	3 / N		
	Sea transport (IMDG)			
	Class(es) :	3		
	EmS-No. :	F-E / <u>S-E</u>		
	Hazard label(s) :	3 / N		
	Air transport (ICAO-TI / IATA-DGR)			
	Class(es) :	3		
	Hazard label(s) :	3		
14.4	Packing group			
	III			
14.5	Environmental hazards			
	Land transport (ADR/RID): Yes			
	Sea transport (IMDG): Yes (P)			
	Air transport (ICAO-TI / IATA-DGR) :	Yes		
14.6	Special precautions for user			
	See protective measures under chapter 7 a	and 8.		
14.7	Transport in bulk according to	Annex II of MARPOL and the IBC Code		
	Not classified for this transport way.			
	Additional information			
	N = Marine Pollutant mark required (all tra	ansport ways).		
SEC	TION 15: Regulatory information	n		
JEC	TON 13. Regulatory information			

# <sup>15.1</sup> Safety, health and environmental regulations/legislation specific for the substance or mixture

## EU legislation Authorisations and/or restrictions on use To follow : REACH, Annex XVII, No. 3

## National regulations

Water hazard class (WGK)

Class: 2 Classification according to AwSV

## Additional information

Registration status Ingredients/product listed in the following inventories: EINECS/ELINCS (Europe) TSCA (USA) DSL (Canada) ENCS (Japan) AICS (Australia) NZIOC (New Zealand) IECSC (China) KECL (South Korea)

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) : Supersedes date :

SCHWEGmann (

4.0.0 (3.1.0) 25.07.2018

PICCS (Philippines) TCSI (Taiwan) Denmark: PR-No. 1663800

## 15.2 Chemical Safety Assessment

A chemical safety assessment has not been carried out for this product (mixture).

## **SECTION 16: Other information**

### Indication of changes

02. Precautionary statements · 08. Exposure controls/personal protection · 15. Regulatory information

Abbreviations and acronyms AGS: Ausschuss für Gefahrstoffe (German Commission on Hazardous Substances) TRGS: Technical Rules of Hazardous Substances RCP: Reciprocal calculation-based procedure VOC: Volatile Organic Compounds ISO: International Standards Organization EN: European Standard LGK: German storage class ADR: Accord européen relatif au transport international des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail) IMDG-Code: International Maritime Code for Dangerous Goods GGVSee: German Carriage of Dangerous Goods by Sea Ordinance GGVSEB: German Carriage of Dangerous Goods b road, rail and inland waterways ICAO-TI: International Civil Aviation Organization-Technical Instructions IATA-DGR: International Air Transport Association-Dangerous Goods Regulations EINECS: European Inventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances TSCA: Toxic Substances Control Act ENCS/MITI: Japanese Existing and New Chemical Substances List / Ministry of International Trade and Industry DSL: Canadian Domestic Substance List KECL/KECI: Korean Existing Chemicals List / Korea Existing Chemicals Inventory IECSC: Inventory of Existing Chemical Substances in China AICS: Australian Inventory of Chemical Substances PICCS: Philippine Inventory of Chemicals and Chemical Substances NZIoC: New Zealand Inventory of Chemicals TCSI: Taiwan's Chemical Substance Inventory WGK: German Water pollution classification AwSV: German ordinance on installations handling substances hazardous to water BetrSichV: German Ordinance on Industrial Safety and Health GefStoffV: German Hazardous Substances Ordinance PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent, very Bioaccumulative CAS: Chemical Abstracts Service EG/EU: European Union **UN: United Nations** CLP: classification labelling and packaging TWA: Time weighted Average STEL: Short term exposure limit Key literature references and sources for data <sup>1</sup> http://www.baua.de

<sup>2</sup> http://publikationen.dguv.de

<sup>3</sup> http://echa.europa.eu/en/candidate-list-table

The product is classified and labelled according to EC legislation.

## Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

## SCHWEGmann 🤄

Trade name : Revision date : Print date : SCHWEGO<sup>®</sup> mar 8300 25.07.2018 25.07.2018

Version (Revision) :	4.0.0 (3.1.0)
Supersedes date :	25.07.2018

 Classification according to Regulation (EC) № 272/2008 [CLP]:

 Physical hazards: Flash point (°C)

 Health hazards : Calculation method.

 Environmental hazards : Calculation method.

 Relevant H- and EUH-phrases (Number and full text)

 H226
 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## **Training advice**

Special training for first aid necessary.

### **Additional information**

Please refer to our internet website for more information: http://www.schwegmannnet.de

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.