

# PROMOCLEAN™ TP 188



## FEATURES

**PROMOCLEAN™ TP 188** was specially developed to clean and remove varnish, resist, lacquer and paint from all metals used in industry.

**PROMOCLEAN™ TP 188** contains no aromatic or chlorinated components, emulsifying agents or other complex chemical compounds.

It may be used at ambient temperature and up to 15°C below its flash point.

**PROMOCLEAN™ TP 188** has low volatility and is ready to use.

## SPECIFICATIONS

Characteristics	Unit	Value	Method
Appearance	-	Yellow	Visual
Density at 20°C	g/ml	1.04 ± 0.01	MO 0810
Water content	% weight	< 0.3	MO 0610

## CHARACTERISTICS

Property	Unit	Value
Solubility in water	-	partial
Solubility in alcohol	-	total
Flash point	°C	+ 84°C

## PACKAGING TYPE

Available in 20 kg container and 210 kg drum.

## STORAGE & SHELF LIFE

Store product in closed container.  
Storage life: 18 months.

## PROCESS PARAMETERS

**PROMOCLEAN™ TP 188** is ready to use and should preferably be used with machines equipped with Teflon seals.

Do not spray product. Provide good ventilation if used hot.

Wear suitable safety glasses and gloves.

Refer to product safety data sheet for more information.

## HSE

Read the product safety data sheet before using **PROMOCLEAN™ TP 188**. You must take all necessary precautions to prevent fire and explosion. People who handle or are otherwise exposed to the product must wear the personal protection gear recommended in the product safety data sheet.

**PROMOCLEAN™ TP 188** has very little impact on the environment and releases few fumes at use temperature. It does not deplete the ozone layer. The product's low miscibility in water makes it easily biodegradable.

*The information contained in this product sheet is given for indicative purposes and in no way incurs the liability of INVENTEC. All users are liable, with respect to Administrative Authorities (regulation of facilities classified for the protection of the environment) for the compliance of their installation.*

FPW.SB.10109 001 - 23/05/2012