

TAR OFF ECO

DESCRIPTION

A powerful and strong GREEN WORLD and READILY BIODEGRADABLE cleaning product that effectively and rapidly dissolves residues from asphalt, tar, rubber, grease and oil.

Tar Off Eco is renewable (88%) and also 100% readily biodegradable.

PROPERTIES

- Easily removes deposits of tar, bitumen, grease, oil etc. from a variety of surfaces.
- Safe to use on most surfaces as metals, glass, concrete and most plastic and painted surfaces.
- Leaves a shiny surface that should make it harder for dirt (bitumen) to adhere to.
- Does not contain silicone.
- Extremely slow evaporation causes the asphalt stains to remain soft.
- The product must be used undiluted.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.
- A VEIDEC product is to be considered "Readily Biodegradable" when at least 99% of its constituent substances has the natural ability to fully biodegrade in a set timeframe, tested in accordance with set standards. Tar Off Eco is 100% Readily Biodegradable!

FIELD OF APPLICATION

- Suitable for most types of degreasing and cleaning problems.
- Is ideal for cleaning oil or grease stains from machine parts and other equipment.
- Spray on vehicle body parts to remove asphalt, oil residues, in engine compartment, fuel residues from tank lids.
- Clean truck chains, machine parts and anything else that's very greasy.
- An excellent replacement for traditional solvent based cleaning products.
- Depending on the application, Tar Off Eco should be tested for the compatibility with coatings, plastics and elastomer materials.

USER INSTRUCTIONS

1. Spray on surface to be cleaned.
2. Let Tar Off Eco work for 2 to maximum 5 minutes to dissolve the residues. If the surface is deemed safe for the product the working time can be increased.
3. Clean with water.

**TAR OFF ECO – TOE – 130****Art.no. 25124 - 25127**

Signature: JH

Date: 2022-02-24

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

TAR OFF ECO

TECHNICAL DETAILS

Color:	Clear.
Packaging:	500 ml alu can aerosol: Art.no: 25124 5 liters Eco Box: Art.no: 25125 15 liters Eco Box: Art.no: 25126 200 liters drum: Art.no: 25127
Accessories:	Tap 5l Eco Box: Art.no. 35204 Air Mix Tar Off Eco: Art.no. 15215-11 Tap 200l: Art.no. 35227 Pump 200l: Art.no. 35223
Odor:	Mild.
pH value:	N/A
VOC (directive 2010/75/EU):	20,0 % aerosol 0 % bulk
Readily Biodegradable:	100%
Density (20°C):	Ca 0.85 g/l.
Shelf life (temp.) months (+5°C to +25 °C):	12 months.
Application & Surface temperature:	+5°C to +65°C
Certificates & Registrations:	GREEN WORLD, READILY BIODEGRADABLE, GREEN PROPELLANT, BASTA, Kemikaliesvepet.
Others:	In compliance with the legal regulations, please see current Material Safety Data Sheet. https://veidec.com/en/msds
User Instruction:	Scan the QR-code for MSDS, video and other information.



CERTIFICATES/REGISTRATIONS



GREEN WORLD



READILY BIODEGRADABLE.


 GREEN PROPELLANT
(aerosol).

 Tar Off Eco is registered by
BASTA.

FEATURES



UP-AND-DOWN (aerosol).

TAR OFF ECO – TOE – 130

Art.no. 25124 - 25127

Signature: JH

Date: 2022-02-24

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.