

# POWER LUBE PLUS

## DESCRIPTION

A special developed long-term, high-temperature, high-pressure resistant, anti-seize lubricant without pictograms.

Green World (bulk) and NSF H2 food grade approved. Is free of lead and other toxic heavy metals.

Preparation of an organic thickener in mineral oil with additives.

## PROPERTIES

- Withstands extremely high pressures and temperatures.
- Excellent adhesion, water-repellent and lubricating with long-lasting effect.
- Reduces friction through a ball bearing effect.
- It prevents seizing of threaded connections like lambda-sensors etc.
- Considerable time is saved during repairs and maintenance.
- Twin featured both a lubricant and protective anti-corrosion agent.
- Prevents contact corrosion, i.e. galvanic currents between different metals.
- Practical with brush mounted in the lid (125 g).
- Free from nickel, lead and silicone.
- Green certified propellant with CO2 reduction up to 90%, naturally produced via organic waste = Green Propellant.

## FIELD OF APPLICATION

- Prevents common problems such as corrosion, cutting, wear and tear. Problems that arise in most sectors.
- Simplifies assembly and above all else dismantling.
- Applied preventively to prevent unnormal wear and tear of brakes, reduction of brake power, squealing and screeching in the area of the brakes, corrosion at screws and slide pins.
- Apply on brake pads and other moving brake parts.
- When changing spark plugs and mounting of lambda sensors.
- To apply onto wheel nuts and bolts.
- For threaded joints at exhausts and catalytic converter installations.
- As corrosion protection on threaded engine installation parts, gearboxes, axles and at exhaust system installations.

## USER INSTRUCTIONS

Apply on dry and clean substrates, free of loose particles.



POWER LUBE PLUS – PLP - 133

Art.no. 20416-20418

Signature: JH

Date: 2022-03-07

This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.

# POWER LUBE PLUS

## TECHNICAL DETAILS

<b>Color:</b>	Grey.
<b>Packaging:</b>	125 g plastic bootle w brush: Art.no. 20416 450 g plastic bucket : Art.no. 20417 300 ml alu can aerosol: Art.no. 20418
<b>Odor:</b>	Mineral.
<b>Basic oil:</b>	Mineral oil mixture.
<b>NLGI class:</b>	~2
<b>Density (20°C):</b>	~1,07 g/cm <sup>3</sup>
<b>VOC (directive 2010/75/EU):</b>	0 Vol. % (bulk), 58,4 % (aerosol).
<b>Shelf life (temp.) months (+5°C to +25 °C):</b>	24 months.
<b>Temperature range as lubricant:</b>	-20°C to +150°C
<b>Temperature range as anti-seize agent:</b>	-20°C to +1300°C (solid parts)
<b>Certificates &amp; Registrations:</b>	GREEN WORLD, GREEN PROPELLANT, NSF H2.
<b>Others:</b>	In compliance with the legal regulations, please see current Material Safety Data Sheet. <a href="https://veidec.com/en/msds">https://veidec.com/en/msds</a>
<b>Chemical reaction guide:</b>	Is not suitable to be used on oxygen bottles and acetylene equipments.
<b>User Instruction:</b>	Scan the QR-code for MSDS, video and other information.



### CERTIFICATES/REGISTRATIONS



GREEN WORLD  
(not aerosol)



NSF; Category code H2.  
Reg. no: 163234 & 164203.  
<http://www.nsf.com/USDA/letters/163234.pdf>



GREEN PROPELLANT  
(aerosol)

### FEATURES



UP-AND-DOWN.  
(aerosol)

### SYMBOLS



Shake well before use.  
(aerosol)

POWER LUBE PLUS – PLP - 133

Art.no. 20416-20418

Signature: JH

Date: 2022-03-07

*This product information is property of VEIDEC AB and is not to be forwarded to third persons without our agreement. The product information has been made out according to our experiences; the corresponding distributing company has to point out probable characteristics as to the use of the product as the application fields are often very different. The recommendations as to technical use are not binding and do not justify any contractual relationship and subsidiary obligations under the contract of purchase. They especially do not relieve the buyer from testing our product on his own as to the suitability for the designated field of application.*